

# MATERIAL QUICK REFERENCE

## COUPLER, ADAPTERS AND FITTINGS

---

### *Nylon*

- Good all around/all purpose material, strong.
- Good chemical resistance and excellent mechanical properties.
- Stronger than polypropylene.
- Resists cross threading and most hydrocarbons, solvents, agricultural chemicals and mild acids.
- Temperature range -30°F to 200°F.

### *PVDF*

- Use where ultra high purity is required.
- Resists most corrosive chemicals, acids, bases, salts, solvents, halogens, chlorinated solvents and is an UL94-V0 listing.
- Good choice for high temperatures, applications up to 300°F.
- Can be used in place of SS in many applications.

### *Polypropylene*

- Good chemical and corrosion resistance.
- Resists most acids, chemicals and fertilizers.
- Use from 10°F up to 180°F.

### *Food-Grade Polypropylene*

- White, FDA material.
- Cost effective lightweight replacement SS.
- Temperatures up to 180°F.
- Industry applications include food products, cosmetics, pharmaceutical processing.

## GASKETS

---

### *EPT/EPDM*

- Best choice for most fertilizer and agricultural applications.
- Temperatures up to 212°F.

### *Buna-N*

- General purpose industrial—resistant to oil, hydraulic fluid, petroleum based fluids and water.
- Temperatures up to 250°F.

### *Viton®*

- Superior resistance to most fuels, petroleum based fluids, chemicals and solvents.
- Temperatures up to 350°F.

### *Polyurethane*

- Resists abrasion and tearing.
- Resists many solvents, oils and petroleum based fluids.
- Temperatures up to 180°F.

### *PVC*

- Solvent cementable.
- Permanent installation.
- Resists many chemical solutions.
- Ideal for water transfer.
- Sewage system and pump quick disconnects.
- Use where liquids being transferred will not exceed 140°F.

### *Santoprene*

- Special purpose.
- Excellent resistance to weather.
- Good chemical resistance.
- FDA applications—used for protective caps or plugs for SS adapters and couplers.

### *Stainless Steel*

- 316 Excellent chemical and corrosion resistance.
- Use for food service and processing.
- Conductive.

### *Neoprene®*

- Food grade, FDA applications.
- White color.
- Resistant to many oils and chemicals.
- Temperature up to 220°F.

### *Santoprene®*

- Excellent resistance to weather and many chemicals.
- FDA applications.
- Temperatures up to 275°F.

For Assistance **Phone:** 1-800-634-3078 **Fax:** 440-366-0198  
**E-mail:** Sales@BeeValve.com or TechHelp@BeeValve.com

